

# Package ‘OutlierD’

October 18, 2017

**Version** 1.40.0

**Date** 2007-08-02

**Title** Outlier detection using quantile regression on the M-A scatterplots of high-throughput data

**Author** HyungJun Cho <hj4cho@korea.ac.kr>

**Maintainer** Sukwoo Kim <s4kim@korea.ac.kr>

**Depends** R (>= 2.3.0), Biobase, quantreg

**Description** This package detects outliers using quantile regression on the M-A scatterplots of high-throughput data.

**License** GPL (>= 2)

**URL** <http://www.korea.ac.kr/~stat2242/>

**biocViews** Microarray

**NeedsCompilation** no

## R topics documented:

lcms . . . . .	1
OutlierD . . . . .	2
<b>Index</b>	<b>3</b>

---

lcms	<i>LCMS data</i>
------	------------------

---

### Description

This data set consists of LCMS data with two samples.

### Usage

```
data(lcms)
```

### Format

a matrix for LCMS data, rows=peptides, columns=samples

---

OutlierD	<i>Outlier detection using quantile regression on the M-A scatterplots of high-throughput data</i>
----------	--

---

### Description

This detects outliers using quantile regression on the M-A scatterplots of high-throughput data.

### Usage

```
OutlierD(x1, x2, k=1.5, method="nonlin")
```

### Arguments

x1	one n-by-1 vector for data (n= number of peptides, proteins, or genes)
x2	the other n-by-1 vector for data (n= number of peptides, proteins, or genes)
k	parameter in $Q1-k*IQR$ and $Q3+k*IQR$ , $IQR=Q3-Q1$ , $k=1.5$ (default)
method	one of constant, linear, nonlinear, and nonparametric quantile regression

### Value

x	data and results for outliers
---	-------------------------------

### Author(s)

HyungJun Cho

### Examples

```
data(lcms)
x <- log2(lcms) #log2-tranformation, do normalization if necessary

fit1 <- OutlierD(x1=x[,1], x2=x[,2], method="constant")
fit2 <- OutlierD(x1=x[,1], x2=x[,2], method="linear")
fit3 <- OutlierD(x1=x[,1], x2=x[,2], method="nonlin")
fit4 <- OutlierD(x1=x[,1], x2=x[,2], method="nonpar")

fit3$x[1:10,]

plot(fit3$x$A, fit3$x$M, pch=".", xlab="A", ylab="M")
i <- sort.list(fit3$x$A)
lines(fit3$x$A[i], fit3$x$Q3[i], lty=2); lines(fit3$x$A[i], fit3$x$Q1[i], lty=2)
lines(fit3$x$A[i], fit3$x$LB[i]); lines(fit3$x$A[i], fit3$x$UB[i])
title("Nonlinear")
```

# Index

\*Topic **datasets**

lcms, [1](#)

\*Topic **models**

OutlierD, [2](#)

lcms, [1](#)

OutlierD, [2](#)